

General Product Specification

Dimensions (H/W/D)	105.9 mm / 84.84 mm / 61.98 mm (4.17 in / 3.34 in / 2.44 in)
Weight	6.4 Kg (14 lbs)
Power Input	NAMA compliance 9 – 48 V DC wide range input (Typical 12V DC – 2A)

POS Terminal Specification

CPU / OS	32-bit Secure Microprocessor running Linux-based OS
Display / Touch	3.5" 320 x 480 Pixel Color TFT LCD Capacitive Touch Screen
Contactless Reader	EMV Contactless L1 v2.6 Certified Mifare, Felica VISA PayWave, MasterCard PayPass, AMEX ExpressPay, Discover D-PAS, Inerac Flash, CUP QuickPass, JCB J-speedy
MSR Reader	Vertical Swipe
ICC at bottom	Card insert upward
Front Camera	5 Megapixel
Communication	4G LTE (US band) 4G LTE Band 1, 3, 8, 18, 19, 26 Need to meet AT&T criteria Bluetooth 4.0 Ethernet RJ45 USB OTG Connector USB-C RS232 Connector RJ45 for DEX cable (Audio Jack Connector)
Audio	Speaker
Barcode Reader	Newland EM2096 300 pixel projects bright red light beam

