

## General Product Specification

Dimensions (H/W/D)	195 mm / 200 mm / 65 mm (7.7 Inch / 4.3 Inch / 2.5 Inch)
Weight	6.4 Kg (14 lbs)
Power Input	NAMA compliance 9 – 48 V DC wide range input (Typical 12V DC – 2A)
Environmental	IP54 (Terminal Module front side only) Operating temp 0 – 40 C (32 – 104 F)

## POS Terminal Specification

CPU / OS	High performance MCU / Android 7.x and later
Display / Touch	5" TFT Color Display (1280 x 720) Capacitive Touch
Contactless Reader	ISO14443 type A/B, ISO 18092  Mifare, Felica  VISA PayWave, MasterCard PayPass, AMEX ExpressPay, Discover D-PAS, Inerac Flash, CUP QuickPass, JCB J-speedy
MSR Reader	Vertical Swipe
ICC at bottom	Card insert upward
Front Camera	5 Megapixel (Camera is not in use or engaged by PicoVend software at any time during use)
Communication	4G LTE (US band)  4G LTE Band 2, 4, 5, 7, 12, 13, 25, 26  Need to meet AT&T criteria  Wi-Fi 802.11 a/b/g/n  Bluetooth 3.0  Ethernet RJ45
Antenna	4G: External / WiFi & Bluetooth internal integrated
Audio	Speaker / Microphone / Audio Jack (4 pole)
Barcode Reader	Newland EM2096 300 pixel projects bright red light beam



← 4.3" →

↑  
7.7"

**Hardware  
Dimensions**

↓