

Stockwell 2.0

Spec Sheet



Dimensions (H/W/D)	1.5278 meters / 1.525 meters / 0.6096 meters <i>stair walkers are required - the lifting radius needed is 2.3meters</i>
Number of Shelves	Refrigerated Side - 4 Ambient Side - 4
Shelf Sizes	Refrigerated Side Top Three Shelves - 61.278 (W) X 42.863 (D) Bottom Shelf - 61.278 (W) X 26.988 (D) Ambient Side - 61.278 (W) X 42.863 (D)
Weight	181 kg
Power Input	1 Power Cable System pulls 0.9A at 230V 0.5Amps Refrigerator, 0.4Amps Technology
Connectivity	Optconnect, a dual SIM cellular router. <i>(Stockwell PC and Pico Reader are hard-lined to Optconnect)</i>
Hardware	Wiisper 10 PC PicoCooler OptConnect Neo EU Cameras Meraki Z3 Router

POS Terminal Specification

CPU / OS	High performance MCU / Android 7.x and later
Display / Touch	5" TFT Color Display (1280 x 720) Capacitive Touch
Contactless Reader	ISO14443 type A/B, ISO 18092 Mifare, Felica VISA PayWave, MasterCard PayPass, AMEX ExpressPay, Discover D-PAS, Inerac Flash, CUP Quick-Pass, JCB J-speedy
Magnetic Stripe Reader (MSR)	Vertical Swipe
Integrated Chip Cards (ICC) at bottom	Card insert upward
Front Camera	5 Megapixel
Communication	Neo for Europe Cat 4 Europe and UK 1 x Ethernet LAN Port Router DHCP, Static IP, Firewall, Port redirects Up to 150 mbps, typically 20 - 30 mbps 2.7" x 2.2" x 0.7"
Antenna	4G: External / WiFi & Bluetooth internal integrated
Audio	Speaker / Microphone / Audio Jack (4 pole)
Barcode Reader	Newland EM2096 300 pixel projects bright red light beam

