

365RM Connect



365RM Connect is a new highly flexible all-in-one networking solution to meet all connectivity needs.

- Cellular, ethernet, and failover options
- Templated configurations to meet your specifications
- Meets all PCI requirements with advanced encryption, firewall, VLAN, and centralized management
- Local user interface for static IP assignment
- Data plan options for every application

Technical Specifications

Item	Description
LAN Interface	3 x RJ-45 for 10/100/1000 Mbps LAN Port
WAN Interface	10/100/1000 Mbps and 4G LTE
WLAN	802.11ax, 2.4GHz and 5GHz
SIM	1 2FF Mini SIM Slot
4G Band Support	LTE-FDD: 1/2/3/4/5/7/8/12/13/18/19/20/25/26/28; LTE-TDD: B38/39/40/41; WCDMA: B1/2/4/5/6/8/19; GSM: B2/3/5/8
LTE Throughput	Max 150Mbps (DL) / Max 50Mbps (UL)
Antennas	4 WiFi Antenna, 2 LTE Antenna
WIFI	32 SSID, Auto Channel, Guest SSID, Radio Profiles, 2x2 MIMO, 20/40/80/160 MHz channels, 100 Concurrent users, 24dbM RF Power
Network	PPPoE, DHCP, Static IP, L2TP, PPTP, VLAN
Failover	Automatically switch between WAN/ISP and 5G
Firewall	Layer 7 and Layer 3 firewalls
Other functions	NTP, Port Forwarding
Power supply	DC: 12V/1A; 110V/220V
Power consumption (max.)	< 60W
Cloud controller	Advanced functions via Cloud Controller
Certifications	FCC, CE, UKCA, RCM, PTCRB
Dimensions	6.25 x 3.75 x 1.5 in
Wall mount	The distance between the holes you drill should be 3-15/32 inches or 8.8cm. (Same as Meraki Z3)

