



OEM TOOL LISTING

FOR FUJITSU CASH DISPENSERS



JIS RECOMMENDED

(JAPANESE INDUSTRIAL STANDARD)

It's a little known, but "troublesome" standard, the JIS standard is a Pacific Rim phenomenon. The symptom of the problem is when your standard Philips screwdriver 'hangs up', and doesn't feel quite right. The Philips driver won't go into the JIS screw all the way because the corner radius of the screw is smaller than that of the Philips screwdriver.

This is the primary cause of what we know as 'cam-out'.

Oddly enough, the Philips standard was created to allow this condition so that you knew you had reached maximum torque.



VESSEL TOOLS (MADE IN JAPAN)









MOODY TOOLS (MADE IN USA)

220 SERIES - STANDARD









- Transmits ample tightening force to screws

EDP No.	 (mm)	 (mm)	 (mm)	 (mm)	 (mm)	 (mm)
125351	5.5	0.8	75	5.5	32	156.5
125361	5.5	0.8	100	5.5	32	181.5
125362	5.5	0.8	150	5.5	32	231.5
125352	6.0	0.9	100	6.4	41	200
125353	6.0	0.9	150	6.4	41	250
125354	6.0	0.9	200	6.4	41	300
125355	+ 1		75	5.5	32	156.5
125371	+ 1		100	5.5	32	181.5
125372	+ 1		150	5.5	32	231.5
125356	+ 2		100	6.4	41	200
125357	+ 2		150	6.4	41	250
125358	+ 2		200	6.4	41	300

225 SERIES - INSULATED



- Shank is covered in resin for excellent safety

EDP No.	 (mm)	 (mm)	 (mm)	 (mm)	 (mm)	 (mm)
125382	6.0	0.9	100	8.0	36	75
125383	6.0	0.9	150	8.0	36	755
125389	+ 2		100	8.0	36	75
125390	+ 2		150	8.	36	75

RECOMMENDATIONS



Vessel JIS Short/Long

#9985 7 Piece Vessel #216 Handle JIS Driver Set - Short and Long Lengths, #00 - #1 JIS. Includes all seven of the Vessel sizes. #00 x 75mm (3" Blade Length), #00 x 100mm (4"), #0 x 75mm (3"), #0 x 100mm(4"), #1 x 75mm(3"), #1 x 100mm(4")and #1 x 150mm(6"). Add 80mm (3.25") for the handle.



MDS ADJUSTMENT SHEET

3mm paper sheet for adjusting the thickness sensor.

[ArcaTech #520-020-4711]



FEED GAP TOOL

Tool used for adjusting the feed gap in the Pick Mechanism to the proper setting.

[ArcaTech #520-021-1300]



BELT TENSION GAUGE

Dynamometer used to adjust the belt tension.

[ArcaTech #520-020-4169]

ADDITIONAL RECOMMENDATIONS



ALBANIA EP GREASE

Designed for the grease lubrication of rolling element and plain bearings.

[ArcaTech #520-000-6035]



LOCTITE 222 THREADLOCKER (LOW STRENGTH - 0.50 ML.)

222 Threadlocker is ideal for fastener diameters of 1/4in. (6mm) and smaller. Controlled lubricity for accurate clamp loads.



SUPERMILLION 30 OIL

5" General-purpose with red grips

[ArcaTech #520-000-8440]



4" LED MINI FLASHLIGHT

Compact, rugged. Lanyard.
90,000 micro candella (mcd) output



TELESCOPING MIRROR

head flexes and swivels. Stainless-steel.



TELESCOPING MAGNETIC PICKUP TOOL

Pocket clip. Stainless-steel.



HEX KEY SET

Standard and Metric sets are always valuable to have around.



ArcaTech Systems

1403 S Third Street Ext
Mebane, NC 27302
Telephone: 919.304.0080
FAX: 919.882.9998

ArcaTech Systems Europe Limited

Conference House 152 Morrison Street
Edinburgh EH3 8EB
Scotland
Telephone: +44 870 351 8384
FAX: +44 870 351 8385

ArcaTech Systems India

Level 2 Raheja Center Point
294 CST Road
Bandra Complex – 400 098
Santa Cruz (E), MUMBAI
Telephone: +91 22 6707 8855
FAX: +91 22 6707 8711