

## General Product Specification

Dimensions (H/W/D) 470 mm / 200 mm / 345 mm (18.5 Inch / 7.9 Inch / 13.6 Inch)

Weight 10.9 Kg (24 lbs)

Power Input NAMA compliance  
9 – 48 V DC wide range input (Typical 12V DC – 2A)

Environmental IP54 (Terminal Module front side only)  
Recessed design  
Anti-slip stand with counter mount option  
Operating temp 0 – 40 C (32 – 104 F)

## POS Terminal Specification

CPU / OS High performance MCU / Android 7.x and later

Display / Touch 5" TFT Color Display (1280 x 720) Capacitive Touch

Contactless Reader ISO14443 tpe A/B, ISO 18092

Mifare, Felica

VISA PayWave, MasterCard PayPass, AMEX ExpresPay, Discover D-PAS, Inerac Flash, CUP QuickPass, JCB J-speedy

MSR Reader Vertical Swipe

ICC at bottom Card insert upward

Front Camera 5 Megapixel

Communication 4G LTE (US band)  
4G LTE Band 2,4,5,7,12,13,25,26

Need to meet AT&T criteria

Wi-Fi 802.11 a/b/g/n

Bluetooth 3.0

Ethernet RJ45

Antenna 4G: External / WiFi & Bluetooth internal integrated

Audio Speaker / Microphone / Audio Jack (4 pole)

Barcode Reader Newland EM2096 300 pixel projects bright red light beam

## Bill Validator Specification

Multi-color LED Bezel

300 note capacity

Accepts \$1, \$5, \$10, \$20, \$50 and \$100 bills

